

FOUNDATIONS COLLECTION WITH SETAGRIP™

PRODUCT SPECIFICATION SHEET

ONE
FLOR
USA

PRODUCT INFORMATION		
CONSTRUCTION	LVT - LUXURY VINYL TILE	
PRODUCT	SETAGRIP™	
STANDARD SPECIFICATIONS	ASTM F1700	
CLASSIFICATION	CLASS III PRINT FILM, TYPE B EMBOSSED SURFACE	
OVERALL THICKNESS	3.5MM GAUGE 20MIL WEARLAYER	
FACTORY FINISH	EPT SHIELD+ SCRATCH AND STAIN RESISTANT COATING	
INSTALLATION	SETAGRIP™ NO ADHESIVES	
WARRANTY	20 YEAR	
PACKAGING INFORMATION		
TILE SIZES	12 IN x 24 IN (305 MM x 610 MM)	6 IN x 48 IN (152 MM x 1219 MM)
TILES PER CTN / SF	16 TILES - 32 SF (2.97 SM)	16 TILES - 32 SF (2.97 SM)
SHIPPING WEIGHT PER CTN	29.7 POUNDS (13.49 KG)	29.7 POUNDS (13.49 KG)
PERFORMANCE SPECIFICATIONS		
PRODUCT QUALIFICATIONS	ASTM F 1700	PASS
STATIC COEFFICIENT OF FRICTION	ASTM D2047	≥ 0.6 DRY: NEOLITE or LEATHER / PASS
FLAME TEST - FLAME SPREAD	ASTM E648	≥ 0.45 W/CM² CLASS 1 / PASS
FLAME TEST - SMOKE DENSITY	ASTM E662	≤ 450 / PASS
FLEXIBILITY	ASTM F137	6 MM MANDREL / PASS
THICKNESS	ASTM F386	MAX. ± 0.005 IN AS SPECIFIED / PASS
DIMENSIONAL STABILITY	ASTM F2199	MAX. ± 0.020 IN/LIN. FT. / PASS
HEAT STABILITY	ASTM F1514	MAX. AVG. DELTA E < 8.0 / PASS
LIGHT STABILITY	ASTM F1515	MAX. AVG. DELTA E < 8.0 /PASS
SIZE	ASTM F2421	MAX. ± 0.016 IN/LIN. FT. / PASS
SQUARENESS	ASTM F2421	MAX. ± 0.010 IN / PASS
RESISTANCE TO CHEMICAL	ASTM F925	NO OR SLIGHT CHANGE / PASS
IMPACT SOUND INSULATION	ASTM E492 ASTM E989 ASTM E2179	6 IN SLAB/NO CEILING ASSEMBLY IIC: 56 DELTA IIC: 23
CONTACT INFORMATION		
COMPANY NAME	ONEFLOR USA	
PHONE NUMBER	347.507.1042	
EMAIL	INFO@ONEFLORUSA.COM	
WEBSITE	ONEFLORUSA.COM	

SETAGRIP™
MICRO SUCTION ADHESION TECHNOLOGY

No Click | No Additional Adhesives | No Setting Time
Easy Clean | No Wax/Buf | Sound Friendly
No Odors | 100% Virgin Vinyl