

# CLING COMFORT COLLECTION WITH SETAGRIP™



## PRODUCT SPECIFICATION SHEET

PRODUCT INFORMATION			
CONSTRUCTION	LVT - LUXURY VINYL TILE		
PRODUCT	SETAGRIP™		
STANDARD SPECIFICATIONS	ASTM F1700		
CLASSIFICATION	CLASS III PRINT FILM, TYPE B EMBOSSED SURFACE		
OVERALL THICKNESS	3.5MM GAUGE 12MIL WEARLAYER		
FACTORY FINISH	UV CURED URETHANE FORTIFIED WITH CERAMIC BEAD		
INSTALLATION	SETAGRIP™ NO ADHESIVES		
LIMITED WARRANTY	COMMERCIAL: 10 YEARS RESIDENTIAL: 25 YEARS		
PACKAGING INFORMATION			
TILE SIZES	7 IN x 48 IN (178 MM x 1219 MM) PLANK	6 IN x 36 IN (152 MM x 914 MM) STONE	18 IN x 18 IN (457 MM x 457 MM) STONE
TILES PER CTN / SF	14 TILES - 32.67 SF (3.03 SM)	16 TILES - 24 SF (2.23 SM)	14 TILES - 31.5 SF (2.93 SM)
SHIPPING WEIGHT PER CTN	30.4 POUNDS (13.77 KG)	22.6 POUNDS (10.24 KG)	29.3 POUNDS (13.3 KG)
PERFORMANCE SPECIFICATIONS			
PRODUCT QUALIFICATIONS	ASTM F 1700	PASS	
STATIC COEFFICIENT OF FRICTION	ASTM D2047	≥ 0.6 DRY: NEOLITE or LEATHER / PASS	
FLAME TEST - FLAME SPREAD	ASTM E648	≥ 0.45 W/CM² CLASS 1 / PASS	
FLAME TEST - SMOKE DENSITY	ASTM E662	≤ 450 / PASS	
FLEXIBILITY	ASTM F137	6 MM MANDREL / PASS	
THICKNESS	ASTM F386	MAX. ± 0.005 IN AS SPECIFIED / PASS	
DIMENSIONAL STABILITY	ASTM F2199	MAX. ± 0.020 IN/LIN. FT. / PASS	
HEAT STABILITY	ASTM F1514	MAX. AVG. DELTA E < 8.0 / PASS	
LIGHT STABILITY	ASTM F1515	MAX. AVG. DELTA E < 8.0 / PASS	
SIZE	ASTM F2421	MAX. ± 0.016 IN/LIN. FT. / PASS	
SQUARENESS	ASTM F2421	MAX. ± 0.010 IN / PASS	
RESISTANCE TO CHEMICAL	ASTM F925	NO OR SLIGHT CHANGE / PASS	
IMPACT SOUND INSULATION	ASTM E492 ASTM E989 ASTM E2179	6 IN SLAB/NO CEILING ASSEMBLY IIC: 56 DELTA IIC: 23	
CONTACT INFORMATION			
COMPANY NAME	ONEFLOR USA		
PHONE NUMBER	347.507.1042		
EMAIL	INFO@ONEFLORUSA.COM		
WEBSITE	ONEFLORUSA.COM		



No Click | No Additional Adhesives | No Setting Time  
Easy Clean | No Wax/Buf | Sound Friendly  
No Odors | 100% Virgin Vinyl